

IN THE CLAIMS

Kindly cancel claims 2, 3, 10, 11 and 18, without prejudice, and amend claims 1, 4, 9, 12, 17 and 19 as shown in the following claim listing:

1. (currently amended) A transmitter for transmitting a stream of known symbols and unknown symbols through a transmission channel to a first receiver that receives the transmitted stream of known symbols and unknown symbols distorted by intersymbol interference (ISI) and reduces therein an ISI signal, wherein the transmitter comprises:

a known symbol distribution controller capable of inserting a plurality of known symbol clusters into an outgoing stream of unknown symbols in an optimum distribution in order to improve the performance of the first receiver- ; wherein said known symbol distribution controller is capable of determining a channel order, L, associated with the receiver; and wherein said known symbol distribution controller determines the optimum distribution according to a value of the channel order.

2. (canceled)

3. (canceled)

4. (currently amended) The transmitter as set forth in Claim 3 1 wherein said known symbol distribution controller determines a minimum size of each of the plurality of known symbol clusters according to the value of the channel order.

5. (Original) The transmitter as set forth in Claim 1 wherein said transmitted stream of known symbols and unknown symbols is received by a plurality of receivers and wherein the known symbol distribution controller is capable of determining a plurality of channel orders, L1 through Ln, wherein each channel order is associated with a corresponding one of said plurality of receivers.

6. (Original) The transmitter as set forth in Claim 5 wherein said known symbol distribution controller is capable of determining a maximum one of the plurality of channel orders.

7. (Original) The transmitter as set forth in Claim 6 wherein said known symbol distribution controller determines the optimum distribution according to a value of the maximum channel order.

8. (Original) The transmitter as set forth in Claim 7 wherein said the known symbol distribution controller determines a minimum size of each of the plurality of known symbol clusters transmitted to all of the plurality of receivers according to the value of the maximum channel order.

9. (currently amended) A network comprising:

a plurality of receivers, each of said receivers capable of receiving from a transmission channel an incoming stream of known symbols and unknown symbols distorted by intersymbol interference (ISI), wherein each of said receivers comprises a block decision feedback equalizer capable of receiving the transmitted stream of known symbols and unknown symbols distorted by intersymbol interference (ISI) and reducing therein an ISI signal; and

a transmitter for transmitting a stream of known symbols and unknown symbols through a transmission channel to a first receiver, wherein the transmitter comprises a known symbol distribution controller capable of inserting a plurality of known symbol clusters into an outgoing stream of unknown symbols in an optimum distribution in order to improve the performance of a first receiver-, wherein said known symbol distribution controller is capable of determining a channel order, L, associated with the

first receiver, and wherein said known symbol distribution controller determines the optimum distribution according to a value of the channel order.

10. (canceled)

11. (canceled)

12. (currently amended) The network as set forth in Claim ~~11~~ 9 wherein said known symbol distribution controller determines a minimum size of each of the plurality of known symbol clusters according to the value of the channel order.

13. (Original) The network as set forth in Claim 9 wherein said transmitted stream of known symbols and unknown symbols is received by the plurality of receivers and wherein the known symbol distribution controller is capable of determining a plurality of channel orders, L1 through Ln, wherein each channel order is associated with a corresponding one of said plurality of receivers.

14. (Original) The network as set forth in Claim 13 wherein said known symbol distribution controller is capable of determining a maximum one of the plurality of channel orders.

15. (Original) The network as set forth in Claim 14 wherein said known symbol distribution controller determines the optimum distribution according to a value of the maximum channel order.

16. (Original) The network as set forth in Claim 15 wherein said the known symbol distribution controller determines a minimum size of each of the plurality of known symbol clusters transmitted to all of the plurality of receivers according to the value of the maximum channel order.

17. (currently amended) For use in a network comprising a transmitter and a plurality of receivers, wherein each receiver receives from a transmission channel an incoming stream of known symbols and unknown symbols distorted by intersymbol interference (ISI), and wherein each receiver comprises a block decision feedback equalizer capable of receiving the transmitted stream of known symbols and unknown symbols distorted by intersymbol interference (ISI) and reducing therein an ISI signal, a method of transmitting the known symbols and unknown symbols comprising the steps of:

inserting a plurality of known symbol clusters into an

outgoing stream of unknown symbols in an optimum distribution capable of improving the performance of a first one of the receivers; and

transmitting the stream of known symbols and unknown symbols according to the optimum distribution;

determining a plurality of channel orders, L_1 through L_n , wherein each channel order is associated with a corresponding one of said plurality of receivers; and

determining a maximum one of the plurality of channel orders.

18. (canceled)

19. (currently amended) The method as set forth in Claim ~~18~~ 17 further comprising the step of determining the optimum distribution according to a value of the maximum channel order.

20. (Original) The method as set forth in Claim 19 further comprising the step of determining a minimum size of each of the plurality of known symbol clusters transmitted to all of the plurality of receivers according to the value of the maximum channel order.

21. (Previously presented) The transmitter of Claim 1, wherein the known symbol distribution controller is capable of inserting the plurality of known symbol clusters into a plurality of positions in the outgoing stream of unknown symbols.